

SLEEVED PLUG VALVES



PRODUCT FEATURES

- Robust, bi-directional, fully adjustable in-line and external sealing
- Low emission stem seal
- Cavity free
- Non-lubricated / Maintenance free
- Quarter turn operation

OPTIONS

- Firesafe per API 607
- FE Fugitive Emissions Design
- Full Port
- Steam Jacketed
- Multiport
- EZ-Seal Single Point Adjustment

BODY & PLUG

- Carbon Steel & Stainless Steel, Duplex & Super Duplex Stainless Steels, Monels, Inconels, Hastelloys, Titanium, Zirconium, etc.

AVAILABILITY

- Size: ½" – 24"
- Pressure Class: 150/300/600 Fully Rated
- End Connection: Flanged, Threaded, Socket & Butt Welding

DESIGN AND TEST STANDARDS

ANSI B16.5	API 607	ISO 10423
ANSI B16.10	API 598	ISO 15848-1 CO3
ANSI B16.25	API 641	MSS SP-25
ANSI B16.34	DIN EN 12266	MSS SP-55
ASME B16.42	DIN EN 1092-1	MSS SP-61
ASTM / ANSI / EN	DIN EN 558-1	PED
API 599	EPA Method 21	TA-LUFT

APPLICATIONS



Chemical



Petrochemical



Oil



Gas



Refining



Mining



Pulp & Paper



Steel Making



Power Generation



Mineral Refining



Water



Pharmaceutical



Food & Beverage